# GREMLIN 1972





## The look and feel of success

The original U.S.-built subcompact retains the distinctive styling and superior performance that mark it as a very special automobile and accounts for its success. With greater power and weight than usual in its class, you can still expect close to 500-miles-per-tank fuel economy with the standard six cylinder engine. Visibility and passenger room are outstanding—especially for a motor car that rides on a trim 96" wheelbase with a turning circle of just 32' 8". A new optional 304 CID V-8 engine has been added to complement the standard 232 Six and optional 258 Six. A new, smooth shifting "Torque-Command" automatic transmission is optional. Other transmissions are column and floor mounted manuals. "Adjust-O-Tilt" steering column is now optional for models with automatic transmissions. Other popular options include liftgate rear window, swing-out rear quarter vent windows, fold-down rear seat and a sliding vinyl roof. Tailor a 4-passenger Gremlin to your personal taste—from basic transportation to a luxurious, high-performance sporty car. Just decide what you want.





Left: Gremlin optional custom interior with pleated vinyl seats (std. Gremlin "X" package).









Far left: A big 232 CID 6-cylinder engine is standard on all Gremlin models.

Center left: Spoke-style 14" x 6" wheels with D70 Polyglas® tires are optional.

Left: Handy roof rack option for extra loads. Air deflector option helps keep window clean.



Optional sun roof: opens easily, closes securely. Flip-open rear quarter window, optional (standard on Gremlin "X").



Gremlin "X"—the sharpest, sportiest group of features in one package.

#### **Specifications** Dimensions-Overall Size: Length: 161.25 inches Width: 70.58 inches Height: 51.80 inches (52.40 inches opt. tires) Curb Weight: 2560 lbs. Wheelbase: 96 inches Front Tread: (in inches) (for sixes) and V-8's (57.46) 57.24 Rear Tread: (in inches) (for sixes) and V-8's (57.40) 56.24 Rear Tread: (in inches) (for sixes) and V-8's (57.00) 56.60 Brake Diameter/Total Area: (for sixes) and V-8's 9 inches/153 Sq. in.) 10 inches/167 Sq. in. Turning Diameter: 32.7 feet Front Suspension: Coil Springs, Independent Twin Ball Rear Suspension: Multiple Leaf, Semi-Elliptic Headroom, Front/Rear: 37.9 inches/36.4 inches Legroom, Front/Rear: 40.1 inches/29 inches Shoulder room, Front/Rear 54.9 inches/53.0 inches Hiproom, Front/Rear: 54.9 inches/53.0 inches Cargo Capacity, 4-Pass. Model: 6 Cu. feet (8 with Opt. Space-Saver Spare) Seating: 4 Pass. Model Capacities: Gas Tank: 21 Gallons Engine Oil (with filter): 5 Quarts Engine Cooling (with heater): 10.5 Quarts Manual Transmission: 2.5 Pints for 232 CID Automatic Transmission: 17 Pints Rear Axle: 3.0 Pints Standard Features: Vinyl cover for spare tire Rubber floor mats (carpets with custom interior trim) Weather-Eye heater and defroster Exhaust emission control system Fuel tank vapor emission control system Step-on parking brake Suspended pedals (brake, clutch and accelerator) 2-speed electric windshield wipers Long wearing, easily cleaned vinyl upholstery Plug-in socket for main wiring harness Ash tray, front, ball-bearing Deep-Dip body rust preventive Triple-coat, baked acrylic enamel finish (13 colors) Dual pin stripe (rally stripes optional) Aluminized steel exhaust system 50 amp. "Clear Power" battery (70 optional) 37 amp. alternator (55 with air conditioning) Side-of-car, scissors action tire jack Foam rubber front cushion pad Sway bar, front (V-8 only) Fold Down Rear Seat Back Rear Window Liftgate All-synchromesh, 3-speed manual transmission Heavy duty 10" clutch

#### Safe-Command Features:

· Two front shoulder belts

Time	 chau	Idae	hale	anchor

Two front head restraints

4-way hazard warning signals Automatic Back-up lights

Side-of-car safety markers

High intensity headlights with "Guard-Glo" feature

Inside rear-view mirror with twin ball-joint pivots

Left side rear-view mirror Windshield washers (electric)

Non-glare windshield wipers

Windshield defrosters (heater) Single-unit body construction

Energy-absorbing steering column Deep-dish steering wheel High-strength windshield glass

Tempered side and rear glass

Padded sun visors Padded instrument panel

Padded armrests Double-safety brake system Brake system warning light

Self-adjusting brake linings

Anti-theft ignition, steering and transmission lock with warning buzzer

High strength door locks Front seat-back lock

Tire tread-wear indicators

Flush-contoured outside door handles

### Options

	wer and Performance: Power steering Power brakes Power disc brakes, front with 14" wheels only Manual disc brakes, front with 14" wheels only Twin grip differential Quick ratio manual steering (20:1)
Co	onvenience:
	Stowage/litter container
	Air conditioning system: 6.45 x 14 unbelted black tires,
	55-amp. alternator, heavy duty engine cooling, 50-amp.
	battery
	Air conditioning package: Air conditioning system plus
	power steering, tinted glass and insulation group
	Tinted glass, all windows or windshield only Liftgate air deflector
	Liftgate air deflector
	Luggage rack, roof
	Rear quarter vent windows
	Sun roof
片	Adjust-O-Tilt steering wheel, automatic transmission only
П	Interior appointment package: package tray, glove box
	lock and light, cigarette lighter Visibility group: remote control mirror, visor vanity
L	mirror, day/nite rearview mirror, inside hood release,

#### Appearance and Trim:

Rally stripes in white, gold, blue or black

Deluxe variable speed electric wipers

buzzer and door light switches

□ Space-saver tire with 14" wheel only

Gremlin "X" package: spear side decal, painted grille, slot style wheels, D70 x 14 black tires, Space-saver tire, custom interior w/bucket seats, 15" sports steering wheel, interior appointment package and special decals

deluxe variable speed electric wipers and dual horns

Light group: two courtesy lights, brake light, lights-on

seat vinyl, carpeting, cargo area insulation, custom steering wheel, wheel opening moldings and drip moldings Custom steering wheel Sports steering wheel, 3 spokes, 15" Wheel covers (4) Custom wheel covers (4) (14" only)
Turbo-disc wheel covers (4) (14" only)
Spoke-style wheels (4) 14" x 16"—Incl. Space-saver
tire w/regular 14" wheel Decor group: wheel opening moldings, drip moldings and rocker panel moldings, with Gremlin "X" package or custom trim package Protection Items: Bumper guards, front only or front & rear Insulation group: undercoating and hood insulation Clear vinyl floor protection mats Scuff molding-side with vinyl insert ☐ Locking gas cap Heavy Duty Items: ☐ Engine cooling system: heavy duty radiator, power-flex fan and fan shroud 70-amp. battery Handling package: heavy duty springs and shocks plus front sway bar on 6-cylinder models, H.D. springs and shocks on V-8's Front sway bar, 6 cyl. (std. on V-8) ☐ Engine block heater ☐ AM Push button radio ☐ AM/FM push button radio 6.00 x 13 unbelted cord tires, blackwall (standard) or whitewall (optional) with 6-cylinder models

☐ Custom trim package: custom door panels and pleated

☐ 6.95 x 14 unbelted cord tires, blackwall (standard) with V-8 models ☐ Nitrox/TCS System—Nitrox and transmission controlled spark system

Export headlamps. (amber or clear lens)

Metric speedometer Locking gas cap Export tool kit

Finned brake drums (9 inch diameter)

Tropical batteries (50 or 60-amp hr. capacities)

Low compression 6 cylinder engines

☐ Touch-up p
☐ Cigarette lig
☐ Dual horns Touch-up paint

Cigarette lighter, separate from appointement package

Equipment and power features, illustrated or described on this brochure, are optional at extra cost unless otherwise specified. Certain equipment items may not be available for all models. American Motors, whose policy is one of continuous improvement, reserves the right to discontinue or change specifications, models, equipment or prices at any time without incurring obligation. This also applies to local assembly or manufacture areas where local content require-

ments may affect standard and/or optional specifications.



Engines	Carb. Type	Net HP @ RPM	Met Torque @ RPM	Compression Ratio & Fuel	Bore & Stroke	Transmissions	Axle Ratios
232 CID Six (1) 7 Bearings (Std.)	1-Barrel	100 @ 3600	185 @ 1800	8.0:1 Reg.	3.75" x 3.50"	3-Speed Manual Column Shift (Std.) (2)	3.08:1 (3.31:1) (3.58:1)
						3-Speed Manual Floor Shift (Std.) (2)	3.08:1 (3.31:1) (3.58:1)
						Torque-Command Automatic on Column (Opt.)	3.08:1 (3.31:1) (3.58:1)
258 CID Six (1) 7 Bearings (Opt.)	1-Barrel	110 @ 3500	195 @ 2000	8.0:1 Reg.	3.75" x 3.90"	3-Speed Manual Floor Shift (2)	3.08:1 (3.31:1) (3.58:1)
						Torque-Command Automatic on Column (Opt.)	3.08:1 (3.31:1)
304 CID V-8 5 Bearings (Opt.)	2-Barrel	150 @ 4200	245 @ 2500	8.4:1 Reg.	3.75" x 3.44"	3-Speed Manual Floor Shift (2)	3.54:1 (3.15:1)
						Torque-Command Automatic on Column (Opt.)	2.87:1 (3.15:1)

ow compression 6 Cylinder Engine Available W/6 Cylinder Engines.

(2) 3-Speed Manual Transmission has fully synchronized gearing with Heavy Duty 10 inch Clutch.